




Metapark

8 752 742 149
4 × 11,5 W, DALI,
asymmetrical beam



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, Rahmenbefestigung mit 3 Edelstahlschrauben, zur Befestigung an Masten Ø 60 - 100 mm, Befestigung mit 2 Zylinderschrauben M8, cable gland: M20, with 8 m cable Ho5RN-F3G1, connecting terminal: 3 pole, highly efficient aluminum reflector, integral driver (AC/DC), wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, weight 5.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	0 W	Housing colour	black RAL 7021
Control gear	DALI	Protection type	IP65
		Protection class	I
		Impact resistance	IK08
		Weight	5,50 kg