




## Metapark

8 753 166 189

6 × 6,3 W, 7204 lm, 3000 K warm white, DALI,  
Street Optic 153° / 89°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, Rahmenbefestigung mit 3 Edelstahlschrauben, Wandbefestigung: 2 Bohrungen Ø 8,5 mm, Abstand 115 mm, cable gland: M20, mit 1 m Gummi-Zuleitung Ho7RN-F5G1, connecting terminal: 5 pole, PMMA Linsen, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B20 > 50.000 h, Beam angle (FWHM): 153° / 89°, luminous flux: 7204 lm, wattage: 53 W, delivered lumens 137 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,148 m<sup>2</sup>, dimensions: Ø 265 mm, width 207 mm, weight 4.3 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

## Specification

Wattage	53 W	Beam angle (FWHM)	153° / 89°
Delivered lumens	137 lm/W	Housing colour	white RAL 9002
Light source	LED 3000 K	Protection type	IP65
Color Rendering Index	CRI > 80	Protection class	II
Colour tolerance	max 2 SDCM	Impact resistance	IK08
Lifetime ta 25° C	L80/B20 > 50.000 h	Windage area	0,148m <sup>2</sup>
Control gear	DALI	Dimensions	Ø 265 mm, width 207 mm
Input voltage AC	220 – 240 V	Weight	4,30 kg
Input voltage DC	220 – 240 V	Max. ambient temperature ta	40°C°
Voltage protection	6 kV L/N   10 kV L/PE		
Luminaires per B16A / C16A	10 / 16		