



Metapark

8 753 747 359

6 × 6,3 W, 4933 lm, 2700 K warm white, Zhaga 18,
lateral wide beam 133° / 65°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, Rahmenbefestigung mit 3 Edelstahlschrauben, zur Befestigung an Masten Ø 60 - 100 mm, Befestigung mit 2 Zylinderschrauben M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient aluminum reflector, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 133° / 65°, luminous flux: 4933 lm, wattage: 48 W, delivered lumens 102 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,168 m², dimensions: Ø 265 mm, width 215 mm, weight 5,2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage	48 W	Beam angle (FWHM)	133° / 65°
Delivered lumens	102 lm/W	Housing colour	black RAL 7021
Light source	LED 2700 K	Protection type	IP65
Color Rendering Index	CRI > 80	Protection class	II
Colour tolerance	max 2 SDCM	Impact resistance	IK08
Lifetime ta 25° C	L80/B10 > 50.000 h	Windage area	0,168m ²
Control gear	Zhaga 18	Dimensions	Ø 265 mm, width 215 mm
Input voltage AC	220 – 240 V	Weight	5,20 kg
Input voltage DC	220 – 240 V	Max. ambient temperature ta	45°
Voltage protection	6 kV L/N 10 kV L/PE		
Luminaires per B16A / C16A	10 / 16		