



Metapark

8 753 758 049

6 × 6,3 W, 3533 lm, 2200 K warm white, asymmetrical beam 60°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, Rahmenbefestigung mit 3 Edelstahlschrauben, zur Befestigung an Masten Ø 60 - 100 mm, Befestigung mit 2 Zylinderschrauben M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient aluminum reflector, integral driver (AC/DC), CRI > 80, 2 SCDM, service life L80/B10 > 50.000 h, luminous flux: 3533 lm, wattage: 48 W, delivered lumens 74 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,168 m², dimensions: Ø 265 mm, width 207 mm, weight 5.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	48 W	Housing colour	silver grey
Delivered lumens	74 lm/W	Protection type	IP65
Light source	LED 2200 K	Protection class	II
Color Rendering Index	CRI > 80	Impact resistance	IK08
Colour tolerance	2 SCDM	Windage area	0,168m ²
Lifetime ta 25° C	L80/B10 > 50.000 h	Dimensions	Ø 265 mm, width 207 mm
Control gear	on / off	Weight	5,20 kg
Input voltage AC	220 – 240 V	Max. ambient temperature ta	45°
Input voltage DC	220 – 240 V		
Voltage protection	6 kV L/N 10 kV L/PE		
Luminaires per B16A / C16A	10 / 16		