





Metaspaces

8 217 366 599  
6 × 8,6 W, 7204 lm, 3000 K warm white, Zhaga 18 -  
up / down,  
Street Optic 36° / 155°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminaire for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, PMMA linsen, integral driver (AC/DC), CRI > 80, Beam angle (FWHM): 36° / 155°, luminous flux: 7204 lm, wattage: 53 W, delivered lumens 137 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,056 m², dimensions: Ø 376 mm, width 112 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.

IP 65 IK 08

Specification

|                            |                         |                             |                        |
|----------------------------|-------------------------|-----------------------------|------------------------|
| Wattage                    | 53 W                    | Beam angle (FWHM)           | 36° / 155°             |
| Delivered lumens           | 137 lm/W                | Housing colour              | white RAL 9002         |
| Light source               | LED 3000 K              | Protection type             | IP65                   |
| Color Rendering Index      | CRI > 80                | Protection class            | II                     |
| Control gear               | Zhaga 18 - oben / unten | Impact resistance           | IK08                   |
| Input voltage AC           | 220 – 240 V             | Windage area                | 0,056m²                |
| Input voltage DC           | 220 – 240 V             | Dimensions                  | Ø 376 mm, width 112 mm |
| Voltage protection         | 6 kV L/N   8 kV L/PE    | Weight                      | 5,00 kg                |
| Luminaires per B16A / C16A | 10 / 16                 | Max. ambient temperature ta | 45°                    |