




Multispot 1

8 221 058 009

6 W, 273 lm, 2200 K warm white,
extreme narrow beam 5°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser: Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, mounting bracket: 1 elongated hole \varnothing 7 mm, spacing 18 mm, 1 centre hole \varnothing 8.5 mm, tilt range: 170°, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), CRI > 80, max 2 SDCM#, service life L90/B10 > 50.000 h, Beam angle (FWHM): 5°, luminous flux: 273 lm, wattage: 6 W, delivered lumens 46 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0139 m², dimensions: \varnothing 99 mm, width 112 mm, weight 1.3 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	6 W	Beam angle (FWHM)	5°
Delivered lumens	46 lm/W	Housing colour	silver grey
Light source	LED 2200 K	Power supply cable	\varnothing 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM#	Protection class	I
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK08
Control gear	on / off	Windage area	0,0139m ²
Input voltage AC	220 – 240 V	Dimensions	\varnothing 99 mm, width 112 mm
Input voltage DC	220 – 230 V	Weight	1,30 kg
Voltage protection	2 kV L/N 2 kV L/PE	Max. ambient temperature ta	40°
Luminaires per B16A / C16A	50 / 85		