



Multispot 1

8 221 448 029  
0 W, 2200 K warm white,  
medium wide beam 23°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, mounting bracket: 1 elongated hole Ø 7 mm, spacing 18 mm, 1 centre hole Ø 8.5 mm, tilt range: 170°, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 23°, wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0139 m², dimensions (L×H×W): 153 × 185 × 133 mm, weight 1.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

|                            |                      |                             |                    |
|----------------------------|----------------------|-----------------------------|--------------------|
| Wattage                    | 0 W                  | Beam angle (FWHM)           | 23°                |
| Light source               | LED 2200 K           | Housing colour              | black RAL 7021     |
| Colour tolerance           | max 2 SDCM           | Power supply cable          | Ø 6 – 13 mm        |
| Lifetime ta 25° C          | L80/B10 > 50.000 h   | Protection type             | IP65               |
| Control gear               | on / off             | Protection class            | I                  |
| Input voltage AC           | 220 – 240 V          | Impact resistance           | IK08               |
| Input voltage DC           | 220 – 240 V          | Windage area                | 0,0139m²           |
| Voltage protection         | 2 kV L/N   2 kV L/PE | Dimensions                  | 153 × 185 × 133 mm |
| Luminaires per B16A / C16A | 50 / 85              | Weight                      | 1,40 kg            |
|                            |                      | Max. ambient temperature ta | 40°                |