



Multispot 2

8 222 548 099  
9 W, 340 lm, 2200 K warm white,  
asymmetrical beam 67°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, Bügel: 2 Bohrungen Ø 7 mm, Abstand 32 mm, 1 Mittelloch Ø 17 mm, tilt range: 170°, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, luminous flux: 340 lm, wattage: 9 W, delivered lumens 36 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0234 m², dimensions: Ø 123 mm, width 173 mm, weight 2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

|                            |                      |                             |                        |
|----------------------------|----------------------|-----------------------------|------------------------|
| Wattage                    | 9 W                  | Housing colour              | black RAL 7021         |
| Delivered lumens           | 36 lm/W              | Power supply cable          | Ø 6 – 13 mm            |
| Light source               | LED 2200 K           | Protection type             | IP65                   |
| Color Rendering Index      | CRI > 80             | Protection class            | I                      |
| Colour tolerance           | max 2 SDCM           | Impact resistance           | IK08                   |
| Lifetime ta 25° C          | L80/B10 > 50.000 h   | Windage area                | 0,0234m²               |
| Control gear               | on / off             | Dimensions                  | Ø 123 mm, width 173 mm |
| Input voltage AC           | 220 – 240 V          | Weight                      | 2,00 kg                |
| Input voltage DC           | 220 – 240 V          | Max. ambient temperature ta | 40°                    |
| Voltage protection         | 2 kV L/N   2 kV L/PE |                             |                        |
| Luminaires per B16A / C16A | 50 / 50              |                             |                        |