



Multispot 2

8 222 558 169
15 W, 528 lm, 2200 K warm white, DALI,
Vario Optic



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum ALSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, Bügel: 2 Bohrungen Ø 7 mm, Abstand 32 mm, 1 Mittelloch Ø 17 mm, tilt range: 170°, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), CRI > 80, luminous flux: 528 lm, wattage: 15 W, delivered lumens 36 lm/W, protection type IP65, protection class I, impact resistance IKo8, windage area 0,049 m², dimensions: Ø 123 mm, width 210 mm, weight 2.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IKo8

Specification

Wattage	15 W	Housing colour	silver grey
Delivered lumens	36 lm/W	Protection type	IP65
Light source	LED 2200 K	Protection class	I
Color Rendering Index	CRI > 80	Impact resistance	IKo8
Control gear	DALI	Windage area	0,049m²
Input voltage AC	220 – 240 V	Dimensions	Ø 123 mm, width 210 mm
Input voltage DC	220 – 240 V	Weight	2,40 kg
Voltage protection	2 kV L/N 2 kV L/PE		
Luminaires per B16A / C16A	50 / 50		