




Multispot 3

8 223 048 179

0 W, 2200 K warm white, DALI,
linear, rotatable



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, silicon gasket, closure with 2 stainless steel screws, Bügel: 2 Bohrungen Ø 7 mm, Abstand 35 mm, 1 Mittelloch Ø 17 mm, tilt range: 170°, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, windage area 0,031 m², dimensions (L×H×W): 153 × 185 × 133 mm, weight 2.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	0 W	Housing colour	black RAL 7021
Light source	LED 2200 K	Protection type	IP65
Control gear	DALI	Protection class	I
		Impact resistance	IK08
		Windage area	0,031m²
		Dimensions	153 × 185 × 133 mm
		Weight	2,40 kg