



Multispot 2

8 226 146 129

15 W, 1181 lm, 3000 K warm white, DALI, medium wide beam



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), CRI > 80, luminous flux: 1181 lm, wattage: 15 W, delivered lumens 81 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0234 m², dimensions: Ø 123 mm, width 130 mm, weight 2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

|                            |                      |                             |                        |
|----------------------------|----------------------|-----------------------------|------------------------|
| Wattage                    | 15 W                 | Housing colour              | black RAL 7021         |
| Delivered lumens           | 81 lm/W              | Power supply cable          | Ø 6 – 13 mm            |
| Light source               | LED 3000 K           | Protection type             | IP65                   |
| Color Rendering Index      | CRI > 80             | Protection class            | I                      |
| Control gear               | DALI                 | Impact resistance           | IK08                   |
| Input voltage AC           | 220 – 240 V          | Windage area                | 0,0234m²               |
| Input voltage DC           | 220 – 240 V          | Dimensions                  | Ø 123 mm, width 130 mm |
| Voltage protection         | 2 kV L/N   2 kV L/PE | Weight                      | 2,00 kg                |
| Luminaires per B16A / C16A | 50 / 50              | Max. ambient temperature ta | 40°                    |