



Multispot 2

8 226 347 109
8 W, 319 lm, 2700 K warm white, DALI,
extreme narrow beam



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), CRI > 80, luminous flux: 319 lm, wattage: 8 W, delivered lumens 40 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0234 m², dimensions: Ø 123 mm, width 130 mm, weight 2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	8 W	Housing colour	black RAL 7021
Delivered lumens	40 lm/W	Power supply cable	Ø 6 – 13 mm
Light source	LED 2700 K	Protection type	IP65
Color Rendering Index	CRI > 80	Protection class	I
Control gear	DALI	Impact resistance	IK08
Input voltage AC	220 – 240 V	Windage area	0,0234m²
Input voltage DC	220 – 240 V	Dimensions	Ø 123 mm, width 130 mm
Voltage protection	2 kV L/N 2 kV L/PE	Weight	2,00 kg
Luminaires per B16A / C16A	50 / 50	Max. ambient temperature ta	40°