



Multispot 2

8 226 546 069  
15 W, 738 lm, 3000 K warm white,  
Vario Optic



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), CRI > 80, luminous flux: 738 lm, wattage: 15 W, delivered lumens 51 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,049 m², dimensions: Ø 123 mm, width 210 mm, weight 2.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

|                            |                      |                   |                        |
|----------------------------|----------------------|-------------------|------------------------|
| Wattage                    | 15 W                 | Housing colour    | black RAL 7021         |
| Delivered lumens           | 51 lm/W              | Protection type   | IP65                   |
| Light source               | LED 3000 K           | Protection class  | I                      |
| Color Rendering Index      | CRI > 80             | Impact resistance | IK08                   |
| Control gear               | on / off             | Windage area      | 0,049m²                |
| Input voltage AC           | 220 – 240 V          | Dimensions        | Ø 123 mm, width 210 mm |
| Input voltage DC           | 220 – 240 V          | Weight            | 2,40 kg                |
| Voltage protection         | 2 kV L/N   2 kV L/PE |                   |                        |
| Luminaires per B16A / C16A | 50 / 50              |                   |                        |