




## Multispot 3

8 227 058 179

0 W, 2200 K warm white, DALI,  
linear, rotatable



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser: Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, windage area 0,031 m<sup>2</sup>, dimensions (L×H×W): 153 × 185 × 133 mm, weight 2.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

## Specification

Wattage	0 W	Housing colour	silver grey
Light source	LED 2200 K	Protection type	IP65
Control gear	DALI	Protection class	I
		Impact resistance	IK08
		Windage area	0,031 m <sup>2</sup>
		Dimensions	153 × 185 × 133 mm
		Weight	2,40 kg