



Multispot 3

8 227 356 009
15 W, 674 lm, 3000 K warm white,
extreme narrow beam 4° / 41°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 4° / 41°, luminous flux: 674 lm, wattage: 15 W, delivered lumens 45 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0284 m², dimensions: Ø 147 mm, width 138 mm, weight 2.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	15 W	Beam angle (FWHM)	4° / 41°
Delivered lumens	45 lm/W	Housing colour	silver grey
Light source	LED 3000 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	on / off	Windage area	0,0284m²
Input voltage AC	220 – 240 V	Dimensions	Ø 147 mm, width 138 mm
Input voltage DC	220 – 240 V	Weight	2,60 kg
Voltage protection	2 kV L/N 4 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	50 / 85		