



Multispot 3

8 227 768 129
27 W, 1570 lm, 2200 K warm white, DALI,
medium wide beam 26°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 26°, luminous flux: 1570 lm, wattage: 27 W, delivered lumens 58 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0284 m², dimensions: Ø 147 mm, width 137 mm, weight 2.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	27 W	Beam angle (FWHM)	26°
Delivered lumens	58 lm/W	Housing colour	white RAL 9002
Light source	LED 2200 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,0284m²
Input voltage AC	220 – 240 V	Dimensions	Ø 147 mm, width 137 mm
Input voltage DC	220 – 240 V	Weight	2,60 kg
Voltage protection	2 kV L/N 4 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	50 / 85		