




Multispot 3

8 227 958 129

0 W, 2200 K warm white, DALI,  
medium wide beam



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, 2 temperaturwechselbeständige Sicherheitsgläser : Wasserdichter Zwischenraum zur Ergänzung von lichtlenkenden Folien und Wabenrastern, dark screenprint, silicon gasket, closure with 2 stainless steel screws, zur Befestigung an Masten Ø 60 - 100 mm, schwenkbarer Leuchtenfuß aus beschichtetem Aluminium, 2 Bohrungen Ø 9 mm, Abstand 97 mm, 1 Durchgangsloch Ø 13,5 mm, tilt range: 90°, 360° adjustable, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, windage area 0,031 m², dimensions (L×H×W): 153 × 185 × 133 mm, weight 2.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

|              |            |                   |                    |
|--------------|------------|-------------------|--------------------|
| Wattage      | 0 W        | Housing colour    | silver grey        |
| Light source | LED 2200 K | Protection type   | IP65               |
| Control gear | DALI       | Protection class  | I                  |
|              |            | Impact resistance | IK08               |
|              |            | Windage area      | 0,031m²            |
|              |            | Dimensions        | 153 × 185 × 133 mm |
|              |            | Weight            | 2,60 kg            |